

# POWER-XTRA

Model : Power-Xtra Li-ion/Li-Po PCM 25.9V (7 Cell) 25 A\_PCX-L16S30-PX054 Ver: A0 NO: 900.600.501.116

Test item (Test at normal temperature 25±2°C)		Criterion
Voltage	Charging voltage	DC: 29.4V CC/CV (4.2v/Cell) 7s
Supply Current	Normal operating mode current: Fuel gauge in >Sleep Current	NORMAL mode. ILOAD ≤30uA
	Maximal continuous charging current	25A
	Maximal continuous discharging current	25A
	Balance current for single cell	42±10mA
Over-charge Protection (single cell)	Balance voltage for single cell	4.2V±0.05V
	Over charge detection voltage	4.25±0.05V
	Over charge detection delay time	0.5S–2S
	Over charge release voltage	4.05±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.5±0.05V
	Over discharge detection delay time	10–200mS
	Over discharge release voltage	3.0±0.1V
Current protection (Battery pack)	Charge Over current detection current	/
	Detection delay time	/
	Discharge Over current detection current	80±20A
	Detection delay time	5ms–20ms
	Release condition	Cut load, Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-600us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤20mΩ
Temperature	high temperature discharge protection	65°C
	Operating Temperature Range	-40~+85°C
	Storage Temperature Range	-40~+125°C
SIZE: L 105*W 65*T14 mm		
NTC: /	Temperature switch: 65 °C (the batteries temperature)	Weak current switch: /
		