

TECHNICAL INFORMATIONS

Item	Specifications	Conditions
Nominal Voltage	1.2V	
Nominal Capacity	2.000 mAh	Standard charge and Standard discharge
Discharge Cut-off Voltage	1.0V	
Internal Impedance	≤30mΩ	Within 1 hr after standard charge
Charge	Standard	200 mA (0.1C) / Charge at 0.1C for 16 hours / 0°C to 40°C
	Rapid Charge	1.000 mA (0.5C) / ambient temperature of 20±5°C, Relative Humidity: 65±20%
	Trickle Charge	40 ~ 100 mA / (0.02C ~ 0.05C) Ta=-10 ~ 45 °C
Discharge	Standard	400 mA (0.2C) / standard charge, the final voltage is 1.0V
	Rapid Discharge	1.000 mA (0.5C) / standard charge, the final voltage is 1.0V
	Maximum Discharge	1.000 mA (0.5C) Rapid discharge, the final voltage is 0.8V
Over-charge	No leakage nor explosion apacity≥100%	0.2C discharge to 1.0V , 0.1C charge for 48 hrs, then test the Capacity with Standard discharge Conditions
Over-discharge	80%. No leakage nor explosion Capacity≥1600mAh	0.2C discharge to 1.2V, Cornbine the battery with a 3Ω electric resistance, after stored for a period of 24 hrs, then test the Capacity with Standard discharge Conditions
Charge-retention Rate	Nominal capacity 60%(1200mAh)	Storage a period of 28 days after standard charge, then Standard discharge (0.2C) to 1.0V
Weight	24gr	Approximately
Cycles Test	≥ 500 Cycles	IEC61951-2:2003

ENVIRONMENT PERFORMANCE

Storage Temperature

Within 1 Year-20°C to 25°C

Operation Temperature

Standard Charge15°C ~ 25°C

Fast Charge 0°C ~ 40°C

Discharge 0°C ~ 40°C

