

# POWER-XTRA

Model : Power-Xtra PX334060 650 mAh Li-Polymer Battery with connector

Ver:1.0

NO: 900.869.503.121

## 1 Product Specification (产品技术规格)

No. (序号)	Item (项目)	General Parameter (常规参数)		Remark (备注)
1	Rated Capacity (额定容量)	Typical (标称容量)	650mAh	Standard discharge (0.2C C <sub>5</sub> A) after Standard charge (标准充电后 0.2C <sub>5</sub> A 标准放电)
		Minimum (最小容量)	630mAh	
2	Nominal Voltage (正常电压)	3.7V		Mean Operation Voltage (即工作电压)
3	Voltage at end of Discharge (放电终止电压)	2.75V		Discharge Cut-off Voltage (放电截止电压)
4	Charging Voltage (充电电压)	4.2±0.03V		
5	Internal Impedance (内阻)	≤155mΩ		Internal resistance measured at AC 1KHz after 50% charge (半电态下用交流法测量内阻) The measure must uses the new batteries that within one week after shipment and cycles less than 5 times
6	Standard charge (标准充电)	Constant Current 0.5C <sub>5</sub> A Constant Voltage 4.2V 0.01 C <sub>5</sub> A cut-off (持续电流: 0.5C <sub>5</sub> A 持续电压: 4.2V 截止电流: 0.01 C <sub>5</sub> A)		Charge time : Approx 4.0h (充电时间: 大约 4 个小时)
7	Standard discharge (标准放电)	Constant current 0.2 C <sub>5</sub> A end voltage 2.75V (持续电流: 0.2C <sub>5</sub> A 截止电压: 2.75V)		
8	Fast charge (快速充电)	Constant Current 1C <sub>5</sub> A Constant Voltage 4.2V 0.01 C <sub>5</sub> A cut-off (持续电流: 1C <sub>5</sub> A 持续电压: 4.2V 截止电流: 0.01 C <sub>5</sub> A)		Charge time : Approx 2.5h (充电时间: 大约 2.5 个小时)

# POWER-XTRA

Model : Power-Xtra PX334060 650 mAh Li-Polymer Battery with connector

Ver:1.0

NO: 900.869.503.121

Continuous the table 1 (续表 1)

No. (序号)	Item (项目)	General Parameter (常规参数)	Remark (备注)
9	Fast discharge	Constant current 1 C <sub>5</sub> A end voltage 2.75V	
10	Maximum Continuous Charge Current	1.5 C <sub>5</sub> A	
11	Maximum Continuous Discharge Current	1.5 C <sub>5</sub> A	
12	Operation Temperature Range (工作温度范围)	Charge (充电) : 0~45°C	60±25%R.H. Bare Cell (单体电池储存湿度范围)
		Discharge (放电) : -20~60°C	
13	Storage Temperature Range (储存温度范围)	Less than 1 year: -20~25°C (小于一年: -20~25°C)	60±25%R.H. at the shipment state (出货状态时的湿度范围)
		less than 3 months: -20~40°C (小于3个月: -20~40°C)	
14	Pack Dimension (包装后尺寸)	Height: Max 60.5mm (高度: 最大 60.5 mm)	Initial Dimension (初始尺寸)
		Width: Max 40.5 mm (宽度: 最大 40.5 mm)	
		Thickness: Max 3.35mm (厚度: 最大 3.35mm)	



# POWER-XTRA


Model : Power-Xtra PX334060 650 mAh Li-Polymer Battery with connector

Ver:1.0

NO: 900.869.503.121

Initial Dimension: (初始尺寸)



Units (单位)		mm	PCB (保护板)		IC DW01/ MOS 8205A	
Wire(引线)		1007/24#	L(线长)	100±5	L1 (剥线)	1.0-2.0
T (厚度)		3.3 <sup>+0.2</sup> <sub>-0.2</sub>	W (宽度)	40.0 <sup>+0.5</sup> <sub>-0.5</sub>	H (高度)	60.0 <sup>+1.5</sup> <sub>-1.5</sub>
Drawer (绘图)		Checked (审核)		Approved (批准)		Date (期)
			<b>PL334060 DRAWING</b>			
			Terminal 端子		Molex51021 反向	

# POWER-XTRA

Model : Power-Xtra PX334060 650 mAh Li-Polymer Battery with connector


Ver:1.0

NO: 900.869.503.121

---

## Drawing of Label (标签图)

标签格式如下，日期随订单更改 (月/年)



## Packing 包装

PP 袋单独包装，每箱不超 10KG