

Model: Power-Xtra PX975588 - 3.7V 5000 mAh Li-Polymer Battery (PCM/3A)

Stock Code: 900.869.503.289

TECHNICAL INFORMATION

Item	Specifications	Conditions
Nominal Voltage	3.7±0.05V	0.2C Discharge
Charging	Method	CC-CV
	Voltage	4.20±0.03V
Typ. Capacity	5000 mAh	0.2C discharge
Standard Charge Current	1000 mAh (0.2C)	Constant current 0.2C / end voltage 4.2V
Standard Discharging Current	1000 mAh (0.2C)	Constant current 0.2C / end voltage 2.75V
Max. Discharge Current	2500 mAh (0.5C)	1.0C
Temperature	Charge	0 to +45°C
	Discharge	-20 to +60°C
	Storage	Less than 1 year: -20~25°C less than 3 months: -20~40°C
Weight	83 gr	approximately
Cycles Test	Higher than 70% of the Initial Capacities of the Cells Carry out 500cycle Charging/Discharging in the below condition. ♦Charge: Standard Charge ♦Discharge:0.5C to 2.75 V ♦Rest Time between charge /discharge:30min. ♦Temperature:20±5°C	

PCM PARAMETER PER BATTERY PACK

Item	Content	Criterion
Current	Maximum Charge / Discharge	3.0A
Over charge Protection	Overcharge Det. Voltage	4.30±0.05V
	Overcharge Rel. Voltage	4.10±0.05V
Over charge Protection	Overdischarge Det. Voltage	2.40±0.10V
	Overdischarge Rel. Voltage	3.00±0.1V


Model: Power-Xtra PX975588 - 3.7V 5000 mAh Li-Polymer Battery (PCM/3A)

Stock Code: 900.869.503.289

Dimension Details

Item	Description	Dimension
T	Cell Tab Thickness	9.7 ± 2 mm
W	Cell Tab Width	54.5 ± 2 mm
L	Cell Tab Length	88.0 ± 2 mm
CL	Cable Length Length	100 ± 0.3 mm
P	Connector Model	Do not have

Technical Drawing



Image