


ENERGIZER CR2016

Lithium Coin



Industry Standard Dimensions

mm (inches)



Simulated Application to

Permissible deflection from a flat.


Simulated Application test

Typical Performance at 21°C (70°F)

Schedule:	Typical Drains:	Load	Cutoff
	at 2.9V		2.0V
	(mA)	(ohms)	(hours)
Continuous	0.097	30,000	928

Typical Discharge Characteristics

Load: 30K ohms - Continuous Typical Drain @ 2.9V: 0.097 mA



Specifications

Classification: "Lithium Coin"

Chemical System: Lithium / Manganese Dioxide (Li/MnO₂)

Designation: ANSI / NEDA-5000LC, IEC-CR2016

Nominal Voltage: 3.0 Volts

Typical Capacity: 90 mAh (to 2.0 volts) (Rated at 30K ohms at 21°C)

Typical Weight: 1.9 grams (0.07 oz.)

Typical Volume: 0.5 cubic centimeters (0.03 cubic inch)

Max Rev Charge: 1 microampere

Energy Density: 122 milliwatt hr/g, 464 milliwatt hr/cc

Typical Li Content: 0.036 grams (0.0013 oz.)

UL Listed: MH12454

Shipping: For complete details, please reference: Global (except US): Special Provision A45 of the International

Air Transport Association Dangerous

Goods Regulations

United States: 49 CFR 173.185

- (1) KEEP OUT OF REACH OF CHILDREN. Swallowing may lead to serious injury or death in as little as 2 hours due to chemical burns and potential perforation of the esophagus. Immediately see doctor; have doctor phone (202) 625-3333.
- (2) Battery compartment design. To prevent children from removing batteries, battery compartments should be designed with one of the following methods: a) a tool such as screwdriver or coin is required to open battery compartment or b) the battery compartment door/cover requires the application of a minimum of two independent and simultaneous movements of the securing mechanism to open by hand. Screws should remain captive with the battery door or cover.

Internal Resistance Characteristics


Pulse Test at 21°C (70°F)

Bkgnd Drain: Continuous 30K ohms

0.097 mA @2.9V

Pulse Drain: 2 seconds X 12 times/day

400 ohms 6.8 mA @2.7V



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication.

©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Form No. EBC - 4118H Page 1 of 1